Section 1: Identification

Manufacturer :	Western Material & Design, LLC
Address :	1612 E Walnut, Harrisonville, MO 64701
Telephone # : Emergency # :	(847) 683-4500 1-800-424-9300 Chemtrec
Product Class : Trade Name :	DIVISION 3 Jobsite Supply- JS 621 Grout

Section 2: Hazard Identification

DANGER!

May cause cancer. May cause skin irritation/burns. May cause burns to the eyes. May cause skin sensitization. May cause respiratory irritation.

- H M I S -

Health	: 2
Flammability	: 0
Reactivity	: 0
Personal Protection	:

(Hazard Rating: 0=Least, 1=Slight, 2=Moderate, 3=High, 4=Extreme, *=Chronic)

PRECAUTIONARY STATEMENTS

Avoid direct contact Avoid dust inhalation. Use appropriate Personal Protective Equipment.



Section 3: Hazard Components

		%by	SARA VAPOR PRESSURE LEL				
No.	Component	CAS#	Weight	313	(mm Hg @ 20 C)	(@25 C)	
1.	Microcrystalline Silicon Dioxide	14808-60-7	30-75	NO	N/A	N/A	
2.	Portland Cement	65997-15-1	20-40	NO	N/A	N/A	
3.	Fly Ash	68131 - 74-8	10-20	NO	N/A	N/A	
~				(14 0 0 0			

Component #1 is listed by the IARC and NTP as probably carcinogenic to humans (IARC Group 2A). N/A: = Not Applicable Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR

Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313"

Section 4: First Aid Measures

EYE CONTACT: Immediately flush eyes with water for at least fifteen (15) minutes. Seek medical attention if symptoms persist.

SKIN CONTACT: Remove contaminated shoes and clothing. Wipe excess from skin and flush with water using soap if available. Seek medical attention if irritation occurs. Do not reuse clothing until thoroughly decontaminated. **INHALATION**: Remove victim to fresh air and treat symptomatically. Provide oxygen if breathing is difficult. Give artificial respiration if the victim is not breathing. Seek prompt medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Consult a physician or poison control center and/or transport to an emergency facility immediately

Section 5, Fire-Fighting Measures

FLAMMABILITY CLASSIFICATION

- NFPA: None

- DOT: Not regulated

FLASH POINT: Greater than 750 degrees F.

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or Carbon Dioxide.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS: This product will not burn. Avoid breathing dust if bags are damaged.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None recognized.

Section 6, Accidental Release Measures

SPILL OR LEAK PROCEDURES: LARGE SPILLS>> Evacuate hazard area of unprotected personnel. Wear appropriate dust mask and protective clothing. Shut source of leak only if safe to do so. Avoid inhaling dust. Place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Pick up loose material and place in non-leaking containers; seal tightly for proper disposal.

Section 7, Storage and Handling/PPE

RESPIRATORY PROTECTION: Use ventilation as required to control vapor concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

Section 8, Exposure Controls

		OSHA				ACGIH		
No.	PEL/TWA	PEL/CEILING	PEL/STEL	SKIN	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	+	N/E	N/E	N/E	0.025 mg/m ^{3*}	N/E	N/E	N/E
2.	15 mg/m³*	N/E	N/E	N/E	10 mg/m³	N/E	N/E	N/E
3.	N/A	N/E	N/E	N/E	N/Ē	N/E	N/E	N/E

N/E = Not established * =Respirable Fraction (Nuisance Dust) + = 10 mg/m³ / (%SiO2+2)

Section 9: Physical and Chemical Properties

Boiling Point Evaporation Rate Vapor Density pH Level	: : :	Not established < 1 (ether = 1) > 1 (air = 1) Not applicable	% Volatile by volume % Volatile by weight Weight per gallon	: : :	Not applicable Not applicable Not applicable
--	---------------	---	---	-------------	--

Section 10: Stability and Reactivity

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIALS TO AVOID: None recognized.

HAZARDOUS DECOMPOSITION PRODUCTS: None known. Avoid breathing dust.

Section 11, Toxicological Information

EYE CONTACT: This material may cause mild eye irritation.

SKIN CONTACT: Exposure may cause mild skin irritation. Prolonged or repeated contact may cause redness, burning, drying, and cracking of the skin.

Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

INHALATION: Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes. Based on the presence of component 1 inhalation of Silica dust may cause lung disease (silicosis).

INGESTION: This material may cause irritation of the gastrointestinal tract.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and rednes. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: None recognized

Section 12, Ecological Information

N/A

Section 13, Disposal Considerations

WASTE DISPOSAL: Observe all Federal, State and local regulations regarding proper disposal.

Section 14, Transport Information

N/A

Section 15, Regulatory Information

N/A

Section 16, Other Information

Latest copy produced February 12, 2016